



Kaufmann® Raw Concrete Primer

Technical Data Sheet

Definition

KAUFMANN® Exposed Concrete Primer is an acrylic-based professional exterior primer developed for low-absorption surfaces. It enhances paint adhesion, reduces consumption, and provides a smooth base surface.

Surfaces to be Applied

KAUFMANN® Exposed Concrete Primer is especially suitable for exposed concrete, precast concrete, cement-based plaster, gypsum, putty, drywall, OSB, MDF, and sound previously painted surfaces. It balances the surface's absorption rate, ensuring smoother application and better adhesion of the topcoat.

Product Features & Advantages

- Acrylic emulsion-based
- Water-based and environmentally friendly
- High adhesion strength
- Maximum adhesion on low-absorption surfaces
- Breathable structure
- Reduces paint consumption
- Ensures uniform paint distribution
- Can be applied in a single coat
- Applicable by roller, brush, or airless spray

Application

The surface must be clean, dry, solid, and capable of supporting the paint. Dirt, dust, oil, and loose layers should be completely removed, and necessary surface repairs and corrections performed. Newly plastered or concrete surfaces must cure for 28 days. Kaufmann Primer should be applied before painting. The paint must be applied in at least two coats. During application and full curing, ambient and surface temperatures should be between +5°C and +30°C. Especially in hot weather, avoid painting between 10:00 AM and 4:00 PM or under direct sunlight.

Packaging

17.5 KG





Storage

The product should be stored in its original packaging, protected from freezing, in a cool and dry environment between +5°C and +30°C. The packaging must be kept upright with the lid tightly closed. When stored under appropriate conditions, the shelf life is a minimum of 12 months.

Health and Safety

Please pay attention to the safety warnings on the packaging. A Safety Data Sheet (SDS) is available for this product. The SDS provides detailed information on precautions for use, safety risks, and health-related matters.

Legal Disclaimer

The information in this document is based on Kaufmann laboratory tests and field experience. Kaufmann products are considered semi-finished goods; however, since they may be used outside Kaufmann's control, only the product quality is guaranteed. Changes may be made to the product to comply with local regulations and market requirements. Kaufmann reserves the right to modify the information provided without prior notice.

This product is manufactured by 5K MÜHENDİSLİK and holds compliance certificates for TS EN ISO 10002, TS EN ISO 14001:2015, TS ISO 31000, TS EN ISO 45001, TS ISO 9001:2008, TSE, CE, and Local Production standards.